



CATALOG COTURI INOX SUDATE 90°
CONFORM ASTM – Raza scurtă

Coturi sudate/trase 90°, conform ASTM Raza scurtă (SR) ASTM-A 403 ASME B16.9 Dimensiuni uzuale				
D mm	S mm	ȚOLI - SCH	R	Kg/buc.
33.40	2.77	1" SCH 10S	25.4	0.11
33.40	3.38	1" SCH 40S	25.4	0.13
42.16	2.77	1.1/4" SCH 10S	31.8	0.16
42.16	3.56	1.1/4" SCH 40S	31.8	0.21
48.26	2.77	1.1/2" SCH 10S	38.1	0.22
48.26	3.68	1.1/2" SCH 40S	38.1	0.28
60.33	2.77	2" SCH 10S	50.8	0.48
60.33	3.91	2" SCH 40S	50.8	0.36
73.03	3.05	2.1/2" SCH 10S	63.5	0.52
73.03	5.16	2.1/2" SCH 40S	63.5	0.92
88.90	3.05	3" SCH 10S	76.0	0.84
88.90	5.49	3" SCH 40S	76.0	1.49
114.30	3.05	4" SCH 10S	101.6	1.38
114.30	6.02	4" SCH 40S	101.6	2.65
168.28	3.40	6" SCH 10S	152.4	3.36
168.28	7.11	6" SCH 40S	152.4	6.87
219.08	3.76	8" SCH 10S	203.2	6.57
219.08	8.18	8" SCH 40S	203.2	14.00
273.05	4.19	10" SCH 10S	254.0	11.50
273.05	9.27	10" SCH 40S	254.0	26.25
323.85	4.57	12" SCH 10S	304.8	17.90
323.85	9.53	12" SCH 40S	304.8	40.40