



CATALOG COTURI INOX SUDATE 90°
CONFORM ASTM – Raza lungă

Coturi sudate/trase 90°, conform ASTM Raza lungă (LR) ASTM-A 403 ASME B16.9 Dimensiuni uzuale				
D mm	S mm	ȚOLI - SCH	R	Kg/buc.
21.34	2.11	1/2" SCH 10S	38.1	0.11
21.34	2.77	1/2" SCH 40S	38.1	0.14
21.34	3.73	1/2" SCH 80S	38.1	0.18
26.67	2.11	3/4" SCH 10S	38.1	0.07
26.67	2.87	3/4" SCH 40S	38.1	0.08
26.67	3.91	3/4" SCH 80S	38.1	0.10
33.40	2.77	1" SCH 10S	38.1	0.14
33.40	3.38	1" SCH 40S	38.1	0.15
33.40	4.55	1" SCH 80S	38.1	0.19
42.16	2.77	1.1/4" SCH 10S	47.6	0.23
42.16	3.56	1.1/4" SCH 40S	47.6	0.26
42.16	4.85	1.1/4" SCH 80S	47.6	0.35
48.26	2.77	1.1/2" SCH 10S	57.2	0.30
48.26	3.68	1.1/2" SCH 40S	57.2	0.40
48.26	5.08	1.1/2" SCH 80S	57.2	0.55
60.33	2.77	2" SCH 10S	76.2	0.50
60.33	3.91	2" SCH 40S	76.2	0.70
60.33	5.54	2" SCH 80S	76.2	0.89
73.03	3.05	2.1/2" SCH 10S	95.0	0.79
73.03	5.16	2.1/2" SCH 40S	95.0	1.29
73.03	7.01	2.1/2" SCH 80S	95.0	1.70
88.90	3.05	3" SCH 10S	114.3	1.18
88.90	5.49	3" SCH 40S	114.3	2.14
88.90	7.62	3" SCH 80S	114.3	2.74
114.30	3.05	4" SCH 10S	152.4	2.03
114.30	6.02	4" SCH 40S	152.4	4.03
114.30	8.56	4" SCH 80S	152.4	5.34
141.30	3.40	5" SCH 10S	190.5	3.46
141.30	6.55	5" SCH 40S	190.5	6.51
168.28	3.40	6" SCH 10S	228.6	5.03
168.28	7.11	6" SCH 40S	228.6	10.90
168.28	10.97	6" SCH 80S	228.6	15.30
219.08	3.76	8" SCH 10S	304.8	9.73
219.08	8.18	8" SCH 40S	304.8	21.50
219.08	12.70	8" SCH 80S	304.8	30.90
273.05	4.19	10" SCH 10S	381.0	16.90
273.05	9.27	10" SCH 40S	381.0	38.60
323.85	4.57	12" SCH 10S	457.0	26.30
323.85	9.53	12" SCH 40S	457.0	59.40